

409.00 EUR
incl. 19% VAT, plus [shipping](#)



- JNF532-2930 (3.5 " SBC)
- INTEL® Bay Trail-M N2930 SoC Processor (1.83GHz)
- 1 * SO-DDR-3 Low Voltage (Max 8GB)
- 1 * 2.5" SATA Device (Max Height 9.5 mm)
- 1 * m-SATA SSD Device (Mini PCI-E)
- Application : Gaming,Medical,POS/KIOSK,Industrial Automation, Transportation, Telecom,Networking,I.O.T,AIO

| | |
|-----------------------|---|
| • Dimension (W*H*D) | • 185 * 48 * 142 mm |
| • Construction | • Aluminum housing |
| • Colors | • Black |
| • MB model | • JNF532-2930 (3.5 " SBC) |
| • CPU | • INTEL® Bay Trail-M N2930 SoC Processor (1.83GHz) |
| • BIOS | • AMI UEFI |
| • Memory | • 1 * SO-DIMM slot (Max 8GB) |
| • Storage Space | • 1 * 2.5" SATA Device (Max Height 9.5 mm) • 1 * m-SATA SSD Device (Mini PCI-E) |
| • Display Interface | • 1 * DVI-D • 1 * VGA (Internal pin header) |
| • Network | • 2 * RJ45 (Giga Lan) • WiFi (optional / JBC375F532W-2930-B) |
| • Audio | • 1 * Line out • 1 * Mic in |
| • Front I/O Port | • 2 * USB 2.0 • 4 * COM (2x factory installation, 2x included in accessories) |
| • Rear I/O Port | • 3 * USB 2.0 • 1 * USB 3.0 • 2 * RJ45 • 1 * DVI-D • 1 * VGA |
| • Expansion Interface | • Mini PCI-E # 1 : Half-size (for mini PCIE WIFI module) • Mini PCI-E # 2 : Full-size (for M-SATA SSD) |

| | |
|-----------------|--|
| • Power Source | <ul style="list-style-type: none"> • DC 9~24V Jack input • Adapter : AC_90~240V / DC_12V_5A / 60W |
| • Certification | <ul style="list-style-type: none"> • EMC : CE , FCC • Safety : RoHS , ErP |
| • Environment | <ul style="list-style-type: none"> • Operating Temperature : 0 ~ 40■ • Storage Temperature : -10 ~ 60■ • Vibration During Operation : N/A • Shock During Operation : N/A |
| • Mounting | <ul style="list-style-type: none"> • Wall mounting Kits |
| • Packing | <ul style="list-style-type: none"> • Net Weight■1.4KG • Gross Weight■2.7KG • Color Box Dimension■250(W) x 118 (D) x 295 (H) mm |